

SPECIFICATIONS

Mobile Surveillance Trailer

Details

- **Solar Panels:** 1800W
- **Batteries:** 1600Ah thermal-wrapped batteries
- **Generator:** 3kW back-up auto-start
- **Mast:** 30 ft. electric mast
- **Monitoring:** Remote battery level monitoring
- **Security:** Hitch lock theft prevention
- **Stabilization:** 4 × stabilization supports
- **Power:** DC 24V
- **Approx. Weight:** 3,900 lbs
- **Dimensions:**
 - **Length:** 159"
 - **Width (Closed):** 85"
 - **Width (Open):** 165"
 - **Height (Lowered):** 109.25"



Surveillance Equipment Options

- Rugged fanless NVR w/ extreme temp hard drives (2–4TB, -25°C to 60°C)
- 25× 5MP rapid-tracking pan-tilt-zoom (PTZ) camera
- 5MP analytic PTZ camera with intrusion strobe
- 5MP low-profile dome camera
- 121 dB IP horn
- Managed 8-port PoE switch
- Local service monitor w/ keyboard & mouse
- Remote health monitoring & alerting
- Custom analytic configuration
- Custom VMS integration
- Remote reboot via WattBox
- Time-lapse recording capability (DW Spectrum)

Additional Hardware

- R2100 dual-SIM Cradlepoint w/ external antenna
- Custom branding & design
- LED programmable strobe lighting
- Travel cable: 6 × Cat6 / 2 × 18AWG
- Magnetic quick-release electronic panel

See how mobile surveillance can protect your site today.

LEARN MORE >